Gelbox; Branch; for cables; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; with gel; 221, 2x73 Series; max. 4 mm<sup>2</sup> connectors; max. 4 mm<sup>2</sup> connectors; max. 4 mm<sup>2</sup> connectors; max. 4

thout splicing connectors; Size 2; gray

https://www.wago.com/207-1332















https://www.wago.com/207-1332



## **Application Examples**

- Bathroom installation (DIN VDE 0100-701)
- · Washing facilities/irrigation systems
- Farms and garden centers (DIN VDE 0100-0705)
- Swimming pool areas (DIN VDE 0100-702)
- Parking lot lighting
- Charging stations and lighting systems in ports

## Note on Packaging Unit (PU) and Subpackaging Unit (SPU):

If you order a full PU, you will receive our eco-friendly, sustainable cardboard blisters packed in a shelf-ready box.

If you order a quantity smaller than a full PU, you will receive the eco-friendly, sustainable cardboard blisters without a shelf-ready box.

Please refer to the system description for the splicing connectors that can be used.

#### Your Benefits:

- Easy, fast and safe to use
- · Can be used immediately and accessed again later
- · Silicon-free
- · Label-free
- Suitable for indefinite storage
- The complete system, which consists of gelboxes and WAGO splicing connectors, has been VDE-tested and IPX8-certified.

Connection data	
Connection 1	
Actuation type	Locking system

Physical data	
Width	45.9 mm / 1.807 inches
Height	17.8 mm / 0.701 inches
Depth	33.6 mm / 1.323 inches

Mechanical data	
Design	Size 2
Mounting type	Flying leads
Protection type	IPX8
Suitable	for 4 mm <sup>2</sup> splicing connectors

Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Housing material	Polypropylene
Fire load	0 MJ
Weight	18.4 g

https://www.wago.com/207-1332



## **Environmental requirements**

Ambient temperature (operation) -55 ... +85 °C 0...+40°C Ambient temperature (storage)

Commercial data 48 (4) pcs PU (SPU) Packaging type Box DE Country of origin GTIN 4055143998017 Customs tariff number 85389099990

## **Product classification**

UNSPSC 39121722

## **Environmental Product Compliance**

RoHS Compliance Status Compliant, No Exemption

## Approvals / Certificates

#### General approvals



rungsinstitut

Approval	Standard	Certificate Name
VDE VDE Prüf- und Zertifizie-	EN 60998	400051938

## Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

## Downloads

### **Environmental Product Compliance**

## Compliance Search

**Environmental Product** 

Compliance 207-1332

Documentation		
System Description		
System Description 207 Series Gel boxes	pdf 1156.45 KB	<u>↓</u>
System Description 207 Series Gel boxes	pdf 1191.37 KB	$\downarrow$

Additional Information		
Certificate	pdf 2308.76 KB	$\underline{\downarrow}$
DLG Test Report 7438	pdf 1455.46 KB	<u>↓</u>

https://www.wago.com/207-1332



Bid Text		
207-1332	xml 3.58 KB	$\perp$
207-1331	docx 20.38 KB	$\overline{\downarrow}$

## CAD/CAE-Data

CAD data

2D/3D Models 207-1332

CAE data **ZUKEN Portal** 207-1332



#### **Installation Notes**

## Installation



Open the Gelbox at the side latches.



Place the wired connector in the Gelbox.



Place the wired connector in the Gelbox.



Close the Gelbox.



Close latch securely.



- Open the Gelbox.
- Remove the gel.
- Rewire with new components.



Lift the flap and pull the cover perforation



Press in the perforation on the sides.



Tear off the cover from the perforation.



As a counter display: Bend the rear flap at the fold, straighten it and fix it in the cardboard cut-out



If the flap is not required, tear off from the perforation.

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at:: www.wago.com

Page 4/4 Version 12.04.2025